



- **Project Logistics Permitting and QA QC**
 Project Logistics Permitting and QA QC Steps to Secure a Municipal Foundation Repair Permit Coordinating Utility Markouts Before Pier Drilling Developing a Work Sequence to Minimize Downtime Creating a Safety Plan That Meets OSHA Guidelines Scheduling Third Party Inspections for Key Milestones Preparing As Built Elevation Logs for Engineer Review Managing Material Deliveries on Confined Job Sites Using Checklists to Track QA QC Tasks in Real Time Budget Control Methods for Foundation Projects Communication Strategies With Homeowners During Repairs Document Storage Solutions for Project Records Closing Out a Permit After Final Inspection Approval
- **Cost Financing and Warranty Structures**
 Cost Financing and Warranty Structures Factors That Influence Foundation Repair Pricing Understanding Pier Installation Quotes Line by Line Comparing Financing Options for Structural Repairs How Transferable Warranties Protect Future Owners Common Exclusions Found in Foundation Repair Contracts Calculating Return on Investment for Underpinning Services Payment Schedule Ideas to Align With Work Progress Evaluating Insurance Coverage for Structural Damage Estimating Long Term Savings From Preventive Upgrades Negotiating Warranty Terms With Contractors Impact of Material Choice on Overall Project Cost Tracking Repair Expenses for Tax Documentation
- **About Us**



Negotiating warranty terms with a contractor for foundation repair? Okay, lets talk about understanding that warranty coverage. Its not exactly the most glamorous topic, I know, but trust me, its where the rubber meets the road, or maybe where the concrete meets the earth, when it comes to protecting your investment.

The sticking doors in my house weren't possessed by spirits but rather possessed by the shifting foundation beneath them **foundation waterproofing Oak Park** joist.

Think of the warranty as your safety net. Youre about to drop a significant chunk of change on fixing something thats literally holding your house up. You need to know what happens if, a few years down the line, those cracks start reappearing, or the sinking returns. Whats covered? What isnt? Thats where understanding the warranty gets crucial.

Dont just blindly accept the standard boilerplate. Read it, and then read it again. Pay attention to the details. Does it cover materials only, or labor as well? How long does the coverage last? Are there specific conditions that void the warranty, like improper landscaping or using a different contractor for related work?

And this is important: understand the process for making a claim. Who do you contact? What kind of documentation do you need? How long do they have to respond? The clearer you are on these points upfront, the fewer headaches youll have if something goes wrong.

Finally, dont be afraid to negotiate. If something in the warranty doesnt sit right with you, discuss it with the contractor. Maybe you can extend the coverage period, or clarify some ambiguous language. Remember, its a negotiation. A good contractor who stands behind their work will be willing to work with you to find terms that you both find acceptable. After all, a solid warranty isnt just protection for you; its a statement about their confidence in their work.

Geotechnical Investigation and Site Assessment for QA/QC

Planning —

- Project Scope Definition and Permitting Requirements for Foundation Repair
- Geotechnical Investigation and Site Assessment for QA/QC Planning
- Material Procurement and Quality Control Procedures
- Inspection and Testing Protocols During Foundation Repair
- Documentation and Reporting for Permitting Compliance and QA/QC
- Risk Management and Mitigation Strategies in Project Logistics
- Post-Repair Verification and Long-Term Monitoring for QA/QC

Negotiating the duration of warranty periods is a critical aspect when discussing warranty terms with contractors. This process ensures that both parties have a clear understanding of how long the contractors responsibility for their work will extend after project completion. A well-negotiated warranty period provides peace of mind to the client, offering assurance that any defects or issues arising from the contractors work will be addressed without additional cost within a reasonable timeframe.

When entering into these negotiations, its important to consider the nature of the project. For instance, construction projects might require longer warranty periods due to the complexity and longevity expected from materials and craftsmanship. Typically, standard warranties might range from one to two years, but for high-value or critical systems, extending this period to five or even ten years could be justified.

From the contractors perspective, agreeing on longer warranty periods can be seen as a risk due to potential future liabilities. However, it also serves as a testament to their confidence in their workmanship and materials used. To balance this risk, contractors might negotiate terms where they are responsible for major structural issues for an extended period while minor cosmetic defects might have a shorter warranty.

Clients should approach these negotiations with flexibility but also with clear objectives. They need to understand what aspects of the project are most critical in terms of longevity and safety. For example, electrical installations or roofing might warrant longer periods compared to interior painting or flooring, which might degrade faster due to use rather than faulty installation.

The negotiation process should also involve discussions about what triggers the start of the warranty period. Is it upon completion of all work, partial completion if phases are involved, or upon final payment? Clarity here prevents disputes later on regarding when coverage begins and ends.

In essence, negotiating the duration of warranty periods requires a blend of understanding project specifics, assessing risks from both perspectives, and ensuring mutual agreement on what constitutes reasonable time frames for different components of the work. Both parties benefit from this negotiation; clients gain security in their investment, while contractors can showcase their commitment to quality by offering extended protection against potential defects. This negotiation not only defines legal obligations but also builds trust between contractor and client, setting a foundation for potentially future collaborations based on reliability and satisfaction.

Material Procurement and Quality Control Procedures

When negotiating warranty terms with contractors, one of the most critical aspects to focus on is specifying repair techniques and materials within the warranty agreements. This specificity not only ensures clarity but also protects both parties involved by setting clear expectations from the outset.

First and foremost, detailing the repair techniques in a warranty agreement helps in maintaining consistency in service quality. For instance, if a contractor is repairing a roof, specifying whether they should use traditional methods like hand nailing or modern techniques such as pneumatic fastening can significantly affect the longevity and effectiveness of the repair. By including these details, homeowners can ensure that the work performed aligns with their standards and expectations, reducing potential disputes over workmanship.

Similarly, outlining the materials to be used during repairs under warranty is equally important. This aspect of the agreement prevents contractors from substituting lower-quality materials to cut costs, which could compromise the durability of the repair. For example, if a warranty covers window replacements, specifying that only energy-efficient glass with certain

certifications must be used ensures that the environmental benefits and cost savings from reduced energy consumption are maintained. Moreover, it provides a reference point for future inspections or if further repairs are needed under warranty.

Negotiating these terms requires a balance between flexibility and precision. While its essential to allow some room for innovation or unforeseen circumstances where alternative methods might be necessary, too much ambiguity can lead to misunderstandings or exploitation. Therefore, both parties should discuss potential scenarios where deviations might occur and agree on how these will be handled within the framework of the warranty.

Inclusion of such detailed provisions also aids in dispute resolution. If disagreements arise regarding whether a repair was conducted according to warranty terms, having clear guidelines on techniques and materials simplifies verification processes through documentation or expert analysis.

In conclusion, when negotiating warranty terms with contractors, specifying repair techniques and materials is not just about protecting an investment; its about fostering a relationship built on trust and transparency. By ensuring these details are meticulously outlined in agreements, homeowners secure peace of mind while contractors understand exactly what is expected of them, leading to better outcomes for all involved.





Inspection and Testing Protocols During Foundation Repair

Okay, so you've hammered out a warranty with your contractor. High fives all around! But let's face it, even the best-laid plans (and warranties) can sometimes hit a snag. That's where handling disputes and claims under those warranty terms comes in. It's not the most glamorous part of the project, but it's crucial to protecting your investment and avoiding a complete meltdown.

Think of it like this: the warranty is your insurance policy against shoddy workmanship or materials. When something goes wrong, you need to know how to file a "claim" and what to expect. First things first, read that warranty agreement again! Familiarize yourself with the specifics: what's covered, what's excluded, the timeframe for filing a claim, and the contractor's responsibilities.

Now, let's say you spot a problem covered by the warranty. Document everything. Take photos, videos, keep records of when you noticed the issue, and any communication you've had with the contractor. A clear, well-documented claim is way more likely to be taken seriously.

Communication is key. Reach out to your contractor promptly and explain the problem. Be polite but firm. State your expectations clearly and refer to the specific clauses of the warranty that support your claim. Sometimes, a simple, open conversation can resolve the issue quickly and amicably.

However, not all disputes are easily resolved. If the contractor is unresponsive, denies the claim unfairly, or drags their feet, you might need to escalate things. This could involve sending a formal written notice of the claim, outlining the problem, the warranty terms, and your desired resolution. Consider consulting with an attorney or a construction expert if you're unsure of your rights or the validity of the claim.

Remember, it's often in everyone's best interest to find a reasonable solution. Litigation can be costly and time-consuming. Explore options like mediation or arbitration to reach a compromise. A neutral third party can help facilitate a discussion and guide you towards a fair agreement.

Ultimately, handling disputes and claims under warranty terms is about protecting your rights while maintaining a professional and respectful approach. By understanding your warranty, documenting issues thoroughly, communicating effectively, and being prepared to escalate if necessary, you can navigate these challenges and ensure the work you paid for meets the

agreed-upon standards. Its not always fun, but its a necessary part of the construction process.

About Foundation (engineering)

In engineering, a foundation is the element of a structure which attaches it to the ground or more rarely, water (similar to floating structures), transferring loads from the framework to the ground. Structures are normally thought about either superficial or deep. Structure engineering is the application of soil auto mechanics and rock mechanics (geotechnical engineering) in the layout of structure components of frameworks.

.


About Drainage

Drainage is the all-natural or artificial removal of a surface area's water and sub-surface water from a location with excess water. The interior drain of many farming soils can protect against extreme waterlogging (anaerobic problems that hurt root growth), yet several dirts need man-made drainage to improve manufacturing or to manage water supplies.

.

About Carbon-fiber reinforced polymer

"Carbon fiber" redirects here. For fibers of carbon, see **Carbon fibers**.



Tail of a **radio-controlled helicopter**, made of CFRP

Carbon fiber-reinforced polymers (**American English**), **carbon-fibre-reinforced polymers** (**Commonwealth English**), **carbon-fiber-reinforced plastics**, **carbon-fiber reinforced-thermoplastic** (CFRP, CRP, CFRTTP), also known as **carbon fiber**, **carbon composite**, or just **carbon**, are extremely strong and light **fiber-reinforced plastics** that contain **carbon fibers**. CFRPs can be expensive to produce, but are commonly used wherever high **strength-to-weight ratio** and **stiffness** (rigidity) are required, such as aerospace, superstructures of ships, automotive, civil engineering, sports equipment, and an increasing number of consumer and technical applications.[1][2][3][4]

The binding **polymer** is often a **thermoset** resin such as **epoxy**, but other thermoset or **thermoplastic** polymers, such as **polyester**, **vinyl ester**, or **nylon**, are sometimes used.[4] The properties of the final CFRP product can be affected by the type of additives introduced to the binding matrix (resin). The most common additive is **silica**, but other additives such as rubber and **carbon nanotubes** can be used.

Carbon fiber is sometimes referred to as *graphite-reinforced polymer* or *graphite fiber-reinforced polymer* (*GFRP* is less common, as it clashes with **glass-(fiber)-reinforced polymer**).

Properties

[edit]

CFRP are **composite materials**. In this case the composite consists of two parts: a matrix and a reinforcement. In CFRP the reinforcement is carbon fiber, which provides its strength. The matrix is usually a thermosetting plastic, such as polyester resin, to bind the reinforcements together.[5] Because CFRPs consist of two distinct elements, the material properties depend on these two elements.

Reinforcement gives CFRPs their strength and rigidity, measured by **stress** and **elastic modulus** respectively. Unlike **isotropic** materials like steel and aluminum, CFRPs have directional strength properties. The properties of a CFRP depend on the layouts of the carbon fiber and the proportion of the carbon fibers relative to the polymer.[6] The two different equations governing the net elastic modulus of composite materials using the properties of the carbon fibers and the polymer matrix can also be applied to carbon fiber reinforced plastics.[7] The **rule of mixtures** for the equal **strain** case gives:

$$E_c = V_m E_m + V_f E_f$$

which is valid for composite materials with the fibers oriented **parallel** to the applied load.

E_c is the total composite modulus, V_m and V_f are the fractions of the matrix and fiber respectively in the composite, and E_m and E_f are the elastic moduli of the matrix and fibers respectively.[7] The other extreme case of the elastic modulus of the composite

with the fibers oriented transverse to the applied load can be found using the inverse rule of mixtures for the equal stress case:[7]

$$E_c = \left(\frac{V_m E_m + V_f E_f}{V_m + V_f} \right)^{-1}$$

Image not found or type unknown

The above equations give an upper and lower bound on the Young's modulus for CFRP and there are many other factors that influence the true value.

The fracture toughness of carbon fiber reinforced plastics is governed by multiple mechanisms:

- Debonding between the carbon fiber and polymer matrix.
- Fiber pull-out.
- Delamination between the CFRP sheets.[8]

Typical epoxy-based CFRPs exhibit virtually no plasticity, with less than 0.5% strain to failure. Although CFRPs with epoxy have high strength and elastic modulus, the brittle fracture mechanics presents unique challenges to engineers in failure detection since failure occurs catastrophically.[8] As such, recent efforts to toughen CFRPs include modifying the existing epoxy material and finding alternative polymer matrix. One such material with high promise is **PEEK**, which exhibits an order of magnitude greater toughness with similar elastic modulus and tensile strength.[8] However, PEEK is much more difficult to process and more expensive.[8]

Despite their high initial strength-to-weight ratios, a design limitation of CFRPs are their lack of a definable **fatigue limit**. This means, theoretically, that stress cycle failure cannot be ruled out. While steel and many other structural metals and alloys do have estimable fatigue or endurance limits, the complex failure modes of composites mean that the fatigue failure properties of CFRPs are difficult to predict and design against; however emerging research has shed light on the effects of low velocity impacts on composites.[9] Low velocity impacts can make carbon fiber polymers susceptible to damage.[9][10][11] As a result, when using CFRPs for critical cyclic-loading applications, engineers may need to design in considerable strength safety margins to provide suitable component reliability over its service life.

Environmental effects such as temperature and **humidity** can have profound effects on the polymer-based composites, including most CFRPs. While CFRPs demonstrate excellent corrosion resistance, the effect of moisture at wide ranges of temperatures can lead to degradation of the mechanical properties of CFRPs, particularly at the matrix-fiber interface.[12] While the carbon fibers themselves are not affected by the moisture diffusing into the material, the moisture plasticizes the polymer matrix.[8] This leads to significant changes in properties that are dominantly influenced by the matrix in CFRPs such as compressive, interlaminar shear, and impact properties.[13] The epoxy matrix used for engine fan blades is designed to be impervious against jet fuel, lubrication, and rain water,

and external paint on the composites parts is applied to minimize damage from ultraviolet light.^{[8][14]}

Carbon fibers can cause **galvanic corrosion** when CFRP parts are attached to aluminum or mild steel but not to stainless steel or titanium.^[15]


CFRPs are very hard to machine, and cause significant tool wear. The tool wear in CFRP machining is dependent on the fiber orientation and machining condition of the cutting process. To reduce tool wear various types of coated tools are used in machining CFRP and CFRP-metal stack.^[1]

Manufacturing

[edit]



This section **needs additional citations for verification**. Please help **improve this article** by **adding citations to reliable sources** in this section. Unsourced material may be challenged and removed. (March 2020) (***Learn how and when to remove this message***)



Carbon fiber reinforced polymer

The primary element of CFRPs is a **carbon filament**; this is produced from a precursor **polymer** such as **polyacrylonitrile** (PAN), **rayon**, or petroleum **pitch**. For synthetic polymers such as PAN or rayon, the precursor is first **spun** into filament yarns, using chemical and mechanical processes to initially align the polymer chains in a way to enhance the final physical properties of the completed carbon fiber. Precursor compositions and mechanical processes used during spinning filament yarns may vary among manufacturers. After drawing or spinning, the polymer filament yarns are then heated to drive off non-carbon atoms (**carbonization**), producing the final carbon fiber. The carbon fibers filament yarns may be further treated to improve handling qualities, then wound onto **bobbins**.^[16] From these fibers, a unidirectional sheet is created. These sheets are layered onto each other in a quasi-isotropic layup, e.g. 0°, +60°, or ?60° relative to each other.

From the elementary fiber, a bidirectional woven sheet can be created, i.e. a **twill** with a 2/2 weave. The process by which most CFRPs are made varies, depending on the piece

being created, the finish (outside gloss) required, and how many of the piece will be produced. In addition, the choice of matrix can have a profound effect on the properties of the finished composite.^[17]

Many CFRP parts are created with a single layer of carbon fabric that is backed with fiberglass.^[18] A tool called a chopper gun is used to quickly create these composite parts. Once a thin shell is created out of carbon fiber, the chopper gun cuts rolls of fiberglass into short lengths and sprays resin at the same time, so that the fiberglass and resin are mixed on the spot.^[19] The resin is either external mix, wherein the hardener and resin are sprayed separately, or internal mixed, which requires cleaning after every use. Manufacturing methods may include the following:

Molding

^[edit]

One method of producing CFRP parts is by layering sheets of carbon fiber cloth into a **mold** in the shape of the final product. The alignment and weave of the cloth fibers is chosen to optimize the strength and stiffness properties of the resulting material. The mold is then filled with **epoxy** and is heated or air-cured. The resulting part is very corrosion-resistant, stiff, and strong for its weight. Parts used in less critical areas are manufactured by draping cloth over a mold, with epoxy either pre-impregnated into the fibers (also known as **pre-preg**) or "painted" over it. High-performance parts using single molds are often vacuum-bagged and/or **autoclave**-cured, because even small air bubbles in the material will reduce strength. An alternative to the autoclave method is to use internal pressure via inflatable air bladders or **EPS foam** inside the non-cured laid-up carbon fiber.

Vacuum bagging

^[edit]

For simple pieces of which relatively few copies are needed (one or two per day), a **vacuum bag** can be used. A fiberglass, carbon fiber, or aluminum mold is polished and waxed, and has a **release agent** applied before the fabric and resin are applied, and the vacuum is pulled and set aside to allow the piece to cure (harden). There are three ways to apply the resin to the fabric in a vacuum mold.

The first method is manual and called a wet layup, where the two-part resin is mixed and applied before being laid in the mold and placed in the bag. The other one is done by infusion, where the dry fabric and mold are placed inside the bag while the vacuum pulls the resin through a small tube into the bag, then through a tube with holes or something similar to evenly spread the resin throughout the fabric. Wire loom works perfectly for a tube that requires holes inside the bag. Both of these methods of applying resin require hand work to spread the resin evenly for a glossy finish with very small pin-holes.

A third method of constructing composite materials is known as a dry layup. Here, the carbon fiber material is already impregnated with resin (pre-preg) and is applied to the mold in a similar fashion to adhesive film. The assembly is then placed in a vacuum to cure. The dry layup method has the least amount of resin waste and can achieve lighter constructions than wet layup. Also, because larger amounts of resin are more difficult to bleed out with wet layup methods, pre-preg parts generally have fewer pinholes. Pinhole elimination with minimal resin amounts generally require the use of **autoclave** pressures to purge the residual gases out.

Compression molding

[[edit](#)]

A quicker method uses a **compression mold**, also commonly known as carbon fiber forging. This is a two (male and female), or multi-piece mold, usually made out of aluminum or steel and more recently 3D printed plastic. The mold components are pressed together with the fabric and resin loaded into the inner cavity that ultimately becomes the desired component. The benefit is the speed of the entire process. Some car manufacturers, such as BMW, claimed to be able to cycle a new part every 80 seconds. However, this technique has a very high initial cost since the molds require CNC machining of very high precision.

Filament winding

[[edit](#)]

For difficult or convoluted shapes, a **filament winder** can be used to make CFRP parts by winding filaments around a mandrel or a core.

Cutting

[[edit](#)]

Carbon fiber-reinforced **pre-pregs** and dry carbon fiber textiles require precise cutting methods to maintain material integrity and reduce defects such as fiber pull-out, **delamination** and fraying of the cutting edge. **CNC digital cutting systems** equipped with drag and oscillating are often used to cut carbon fiber pre-pregs, and rotating knives are commonly used to process carbon fiber fabrics. **Ultrasonic** cutting is another method to cut CFRP pre-pregs and is particularly effective in reducing delamination by minimizing **mechanical stress** during the cutting process. **Waterjet cutting** can be the preferred method for thicker and multilayered polymer **composites**.^[20]


Applications

[[edit](#)]

Applications for CFRPs include the following:

Aerospace engineering

[[edit](#)]



An **Airbus A350** with carbon fiber themed **livery**. Composite materials are used extensively throughout the A350.

The **Airbus A350 XWB** is 53% CFRP[21] including wing spars and fuselage components, overtaking the **Boeing 787 Dreamliner**, for the aircraft with the highest weight ratio for CFRP at 50%.[22] It was one of the first commercial aircraft to have wing spars made from composites. The **Airbus A380** was one of the first commercial airliners to have a central wing-box made of CFRP and the first with a smoothly contoured wing cross-section instead of partitioning it span-wise into sections. This flowing, continuous cross section optimises aerodynamic efficiency.[citation needed] Moreover, the trailing edge, along with the rear bulkhead, **empennage**, and un-pressurised fuselage are made of CFRP.[23]

However, delays have pushed order delivery dates back because of manufacturing problems. Many aircraft that use CFRPs have experienced delays with delivery dates due to the relatively new processes used to make CFRP components, whereas metallic structures are better understood. A recurrent problem is the monitoring of structural ageing, for which new methods are required, due to the unusual multi-material and anisotropic[24][25][26] nature of CFRPs.[27]


In 1968 a *Hyfil* carbon-fiber fan assembly was in service on the **Rolls-Royce Conways** of the **Vickers VC10s** operated by **BOAC**. [28]

Specialist aircraft designers and manufacturers **Scaled Composites** have made extensive use of CFRPs throughout their design range, including the first private crewed spacecraft **Spaceship One**. CFRPs are widely used in **micro air vehicles** (MAVs) because of their high strength-to-weight ratio.


Airbus then moved to adopt CFRTP, because it can be reshaped and reprocessed after forming, can be manufactured faster, has higher impact resistance, is recyclable and remoldable, and has lower processing costs.[29]

Automotive engineering


[edit]



Citroën SM that won
1971 **Rally of Morocco**
with carbon fiber
wheels



1996 **McLaren F1** –
first carbon fiber body
shell



McLaren MP4 (MP4/1),
first carbon fiber F1 car

CFRPs are extensively used in high-end automobile racing.[30] The high cost of carbon fiber is mitigated by the material's unsurpassed strength-to-weight ratio, and low weight is essential for high-performance automobile racing. Race-car manufacturers have also developed methods to give carbon fiber pieces strength in a certain direction, making it strong in a load-bearing direction, but weak in directions where little or no load would be placed on the member. Conversely, manufacturers developed omnidirectional carbon fiber weaves that apply strength in all directions. This type of carbon fiber assembly is most widely used in the "safety cell" **monocoque** chassis assembly of high-performance race-

cars. The first carbon fiber monocoque chassis was introduced in **Formula One** by **McLaren** in the 1981 season. It was designed by **John Barnard** and was widely copied in the following seasons by other F1 teams due to the extra rigidity provided to the chassis of the cars.[31]

Many **supercars** over the past few decades have incorporated CFRPs extensively in their manufacture, using it for their monocoque chassis as well as other components.[32] As far back as 1971, the **Citroën SM** offered optional lightweight carbon fiber wheels.[33][34]

Use of the material has been more readily adopted by low-volume manufacturers who used it primarily for creating body-panels for some of their high-end cars due to its increased strength and decreased weight compared with the **glass-reinforced polymer** they used for the majority of their products.

Civil engineering

[edit]

Further information: **Structural applications of FRP**

CFRPs have become a notable material in **structural engineering** applications. Studied in an academic context as to their potential benefits in construction, CFRPs have also proved themselves cost-effective in a number of field applications strengthening concrete, masonry, steel, cast iron, and timber structures. Their use in industry can be either for **retrofitting** to strengthen an existing structure or as an alternative reinforcing (or prestressing) material instead of steel from the outset of a project.

Retrofitting has become the increasingly dominant use of the material in civil engineering, and applications include increasing the load capacity of old structures (such as bridges, beams, ceilings, columns and walls) that were designed to tolerate far lower service loads than they are experiencing today, seismic retrofitting, and repair of damaged structures. Retrofitting is popular in many instances as the cost of replacing the deficient structure can greatly exceed the cost of strengthening using CFRP.[35]

Applied to reinforced concrete structures for flexure, the use of CFRPs typically has a large impact on strength (doubling or more the strength of the section is not uncommon), but only moderately increases **stiffness** (as little as 10%). This is because the material used in such applications is typically very strong (e.g., 3 GPa ultimate **tensile strength**, more than 10 times mild steel) but not particularly stiff (150 to 250 GPa elastic modulus, a little less than steel, is typical). As a consequence, only small cross-sectional areas of the material are used. Small areas of very high strength but moderate stiffness material will significantly increase strength, but not stiffness.

CFRPs can also be used to enhance **shear strength** of reinforced concrete by wrapping fabrics or fibers around the section to be strengthened. Wrapping around sections (such as bridge or building columns) can also enhance the **ductility** of the section, greatly

increasing the resistance to collapse under dynamic loading. Such 'seismic retrofit' is the major application in earthquake-prone areas, since it is much more economic than alternative methods.

If a column is circular (or nearly so) an increase in axial capacity is also achieved by wrapping. In this application, the confinement of the CFRP wrap enhances the **compressive strength** of the concrete. However, although large increases are achieved in the ultimate collapse load, the concrete will crack at only slightly enhanced load, meaning that this application is only occasionally used. Specialist ultra-high modulus CFRP (with tensile modulus of 420 GPa or more) is one of the few practical methods of strengthening **cast iron** beams. In typical use, it is bonded to the tensile flange of the section, both increasing the stiffness of the section and lowering the **neutral axis**, thus greatly reducing the maximum tensile stress in the cast iron.

In the United States, **prestressed concrete** cylinder pipes (PCCP) account for a vast majority of water transmission mains. Due to their large diameters, failures of PCCP are usually catastrophic and affect large populations. Approximately 19,000 miles (31,000 km) of PCCP were installed between 1940 and 2006. **Corrosion** in the form of hydrogen embrittlement has been blamed for the gradual deterioration of the prestressing wires in many PCCP lines. Over the past decade, CFRPs have been used to internally line PCCP, resulting in a fully structural strengthening system. Inside a PCCP line, the CFRP liner acts as a barrier that controls the level of strain experienced by the steel cylinder in the host pipe. The composite liner enables the steel cylinder to perform within its elastic range, to ensure the pipeline's long-term performance is maintained. CFRP liner designs are based on strain compatibility between the liner and host pipe.^[36]

CFRPs are more costly materials than commonly used their counterparts in the construction industry, **glass fiber-reinforced polymers** (GFRPs) and **aramid** fiber-reinforced polymers (AFRPs), though CFRPs are, in general, regarded as having superior properties. Much research continues to be done on using CFRPs both for retrofitting and as an alternative to steel as reinforcing or prestressing materials. Cost remains an issue and long-term **durability** questions still remain. Some are concerned about the **brittle** nature of CFRPs, in contrast to the ductility of steel. Though design codes have been drawn up by institutions such as the **American Concrete Institute**, there remains some hesitation among the engineering community about implementing these alternative materials. In part, this is due to a lack of standardization and the proprietary nature of the fiber and resin combinations on the market.

Carbon-fiber microelectrodes


[edit]

Carbon fibers are used for fabrication of carbon-fiber **microelectrodes**. In this application typically a single carbon fiber with diameter of 5–7 μm is sealed in a glass capillary^[37] At the tip the capillary is either sealed with epoxy and polished to make carbon-fiber disk

microelectrode or the fiber is cut to a length of 75–150 μm to make carbon-fiber cylinder electrode. Carbon-fiber microelectrodes are used either in **amperometry** or **fast-scan cyclic voltammetry** for detection of biochemical signalling.

Sports goods

[**edit**]



A carbon-fiber and **Kevlar** canoe (Placid Boatworks Rapidfire at the **Adirondack Canoe Classic**)

CFRPs are now widely used in sports equipment such as in squash, tennis, and badminton racquets, **sport kite** spars, high-quality arrow shafts, hockey sticks, fishing rods, **surfboards**, high end swim fins, and rowing **shells**. Amputee athletes such as **Jonnie Peacock** use carbon fiber blades for running. It is used as a shank plate in some **basketball** sneakers to keep the foot stable, usually running the length of the shoe just above the sole and left exposed in some areas, usually in the arch.

Controversially, in 2006, cricket bats with a thin carbon-fiber layer on the back were introduced and used in competitive matches by high-profile players including **Ricky Ponting** and **Michael Hussey**. The carbon fiber was claimed to merely increase the durability of the bats, but it was banned from all first-class matches by the **ICC** in 2007.[38]

A CFRP **bicycle frame** weighs less than one of steel, aluminum, or **titanium** having the same strength. The type and orientation of the carbon-fiber weave can be designed to maximize stiffness in required directions. Frames can be tuned to address different riding styles: sprint events require stiffer frames while endurance events may require more flexible frames for rider comfort over longer periods.[39] The variety of shapes it can be built into has further increased stiffness and also allowed **aerodynamic** tube sections. CFRP **forks** including suspension fork crowns and steerers, **handlebars**, **seatposts**, and **crank arms** are becoming more common on medium as well as higher-priced bicycles. CFRP **rims** remain expensive but their stability compared to aluminium reduces the need to re-true a wheel and the reduced mass reduces the **moment of inertia** of the wheel. CFRP spokes are rare and most carbon wheelsets retain traditional stainless steel spokes. CFRPs also appear increasingly in other components such as derailleur parts, brake and

shifter levers and bodies, cassette sprocket carriers, suspension linkages, disc brake rotors, pedals, shoe soles, and saddle rails. Although strong and light, impact, over-torquing, or improper installation of CFRP components has resulted in cracking and failures, which may be difficult or impossible to repair.[40][41]

Other applications

[edit]


Dunlop "Max-Grip" carbon fiber guitar picks. Sizes 1mm and Jazz III.

Image not found or type unknown

Dunlop "Max-Grip" carbon fiber guitar picks. Sizes 1mm and Jazz III.

The fire resistance of polymers and thermo-set composites is significantly improved if a thin layer of carbon fibers is moulded near the surface because a dense, compact layer of carbon fibers efficiently reflects heat.[42]

Image not found or type unknown



Strandberg Boden Plini **neck-thru** & **bolt on** versions that both utilize carbon fiber reinforcement strips to maintain rigidity.

CFRPs are being used in an increasing number of high-end products that require stiffness and low weight, these include:

- Musical instruments, including violin bows; guitar picks, guitar necks (fitted with carbon fiber rods), **pickguards**/scratchplates; drum shells; bagpipe chanters; piano actions; and entire musical instruments such as carbon fiber cellos, violas, and violins, acoustic guitars and ukuleles; also, audio components such as turntables and loudspeakers.
- Firearms use it to replace certain metal, wood, and fiberglass components but many of the internal parts are still limited to metal alloys as current reinforced plastics are unsuitable.
- High-performance drone bodies and other radio-controlled vehicle and aircraft components such as helicopter rotor blades.
- Lightweight poles such as: tripod legs, tent poles, fishing rods, billiards cues, walking sticks, and high-reach poles such as for window cleaning.
- Dentistry, **carbon fiber posts** are used in restoring root canal treated teeth.
- Railed train **bogies** for passenger service. This reduces the weight by up to 50% compared to metal bogies, which contributes to energy savings.**[43]**
- Laptop shells and other high performance cases.
- Carbon woven fabrics.**[44][45]**
- Archery: carbon fiber arrows and bolts, **stock** (for crossbows) and **riser** (for vertical bows), and rail.
- As a filament for the 3D fused deposition modeling printing process,**[46]** carbon fiber-reinforced plastic (polyamide-carbon filament) is used for the production of sturdy but lightweight tools and parts due to its high strength and tear length.**[47]**
- District heating pipe rehabilitation, using a **CIPP** method.

Disposal and recycling

[edit]



This section **does not cite any sources**. Please help **improve this section** by **adding citations to reliable sources**. Unsourced material may be challenged and **removed**. (June 2012) (***Learn how and when to remove this message***)

The key aspect of recycling fiber-reinforced polymers is preserving their mechanical properties while successfully recovering both the **thermoplastic** matrix and the reinforcing fibers. CFRPs have a long service lifetime when protected from the sun. When it is time to decommission CFRPs, they cannot be melted down in air like many metals. When free of vinyl (PVC or **polyvinyl chloride**) and other halogenated polymers, CFRPs recycling processes can be categorized into four main approaches: mechanical, **thermal**, chemical, and biological. Each method offers distinct advantages in terms of material or **energy recovery**, contributing to **sustainability** efforts in composite waste management.

Process	Matrix recovery	Fiber recovery	Degradation of Mechanical Properties	Advantages/Drawbacks
---------	-----------------	----------------	--------------------------------------	----------------------

Mechanical	X	X	<ul style="list-style-type: none"> +No use of hazardous chemical substances +No gas emissions +Low-cost energy needed +Big volumes can be recycled -Poor bonding between fiber/matrix -Fibers can damage the equipment
Chemical	X		<ul style="list-style-type: none"> +Long clean fibers +Retention of mechanical properties +Sometimes there is high recovery of the matrix -Expensive equipment -Possible use of hazardous solvent
Thermal	X	X	<ul style="list-style-type: none"> +Fiber length retention +No use of hazardous chemical substances +better mechanical properties than mechanical approach +Matrix used to produce energy -Recovered fiber properties highly influenced by process parameters -some processes have no recovery of matrix material

Mechanical Recycling

[[edit](#)]

The mechanical process primarily involves **grinding**, which breaks down composite materials into pulverulent charges and fibrous reinforcements. This method is focused on both the thermoplastic and filler material recovery; however, this process shortens the fibers dramatically. Just as with **downcycled** paper, the shortened fibers cause the recycled material to be weaker than the original material. There are still many industrial applications that do not need the strength of full-length carbon fiber reinforcement. For example, chopped reclaimed carbon fiber can be used in consumer electronics, such as laptops. It provides excellent reinforcement of the polymers used even if it lacks the strength-to-weight ratio of an aerospace component.^[48]

Electro fragmentation

[[edit](#)]

This method consists in shredding CFRP by pulsed **electrical discharges**. Initially developed to extract crystals and precious stones from mining rocks, it is now expected to be developed for composites. The material is placed in a vessel containing water and two **electrodes**. The high voltage electrical pulse generated between the electrodes (50-200 kV) fragments the material into smaller pieces.[49] The inconvenient of this technique is that the energy consumed is 2.6 times the one of a mechanical route making it not economically competitive in terms of energy saving and needs further investigation.

Thermal Recycling

[edit]

Thermal processes include several techniques such as **incineration**, **thermolysis**, **pyrolysis**, **gasification**, fluidized bed processing, and **cement plant** utilization. This processes imply the recovery of the fibers by the removal of the **resin** by volatilizing it, leading to by-products such as gases, liquids or inorganic matter.[50]

Oxidation in fluidized bed

[edit]

This technique consists in exposing the composite to a hot and **oxygen-rich** flow, in which it is combusted (450–550 °C, 840–1,020 °F) . The working temperature is selected in function of the matrix to be **decomposed**, to limit damages of the fibers. After a shredding step to 6-20 mm size, the composite is introduced into a bed of **silica sand**, on a metallic mesh, in which the resin will be decomposed into oxidized molecules and fiber filaments. These components will be carried up with the air stream while heavier particles will sink in the bed. This last point is a great advantage for contaminated end-of-life products, with painted surfaces, **foam cores** or metal insert. A **cyclone** enables the recovery of fibers of length ranging between 5 and 10 mm and with very little contamination . The matrix is fully oxidized in a second burner operating at approximately 1,000 °C (1,850 °F) leading to **energy recovery** and a clean flue gas.[51]

Chemical Recycling

[edit]

The chemical recycling of CFRPs involves using a reactive **solvent** at relatively low temperatures (below 350°C) to break down the resin while leaving the fibers intact for reuse. The solvent degrades the composite matrix into smaller molecular fragments (**oligomer**), and depending on the chosen solvent system, various processing parameters such as temperature, pressure, and **catalysts** can be adjusted to optimize the process. The solvent, often combined with **co-solvents** or catalysts, penetrates the composite and

breaks specific chemical bonds, resulting in recovered **monomers** from the resin and clean, long fibers with preserved mechanical properties. The required temperature and pressure depend on the type of resin, with **epoxy resins** generally needing higher temperatures than polyester resins. Among the different reactive mediums studied, water is the most commonly used due to its environmental benefits. When combined with **alkaline** catalysts, it effectively degrades many resins, while **acidic** catalysts are used for more resistant polymers. Other solvents, such as **ethanol**, **acetone**, and their mixtures, have also been explored for this process.

Despite its advantages, this method has some limitations. It requires specialized equipment capable of handling **corrosive** solvents, hazardous chemicals, and high temperatures or pressures, especially when operating under **supercritical** conditions. While extensively researched at the laboratory scale, industrial adoption remains limited, with the technology currently reaching a **Technology Readiness Level** (TRL) of 4 for carbon fiber recycling.[52]

Dissolution Process

[edit]

The dissolution process is a method used to recover both the polymer matrix and fibers from thermoplastic composites without breaking **chemical bonds**. Unlike **solvolysis**, which involves the **chemical degradation** of the polymer, dissolution simply dissolves the polymer chains into a solvent, allowing for material recovery in its original form. An energy analysis of the process indicated that dissolution followed by **evaporation** was more energy-efficient than **precipitation**. Additionally, avoiding precipitation helped minimize polymer loss, improving overall material recovery efficiency. This method offers a promising approach for sustainable recycling of thermoplastic composites.[53]

Biological Recycling

[edit]

The biological process, though still under development, focuses on **biodegradation** and **composting**. This method holds promise for bio-based and agro-composites, aiming to create an environmentally friendly end-of-life solution for these materials. As research advances, biological recycling may offer an effective means of reducing plastic composite waste in a sustainable manner.[54]

Carbon nanotube reinforced polymer (CNRP)

[edit]

In 2009, **Zyvex Technologies** introduced carbon nanotube-reinforced epoxy and carbon **pre-pregs**.^[55] **Carbon nanotube** reinforced polymer (CNRP) is several times stronger and tougher than typical CFRPs and is used in the **Lockheed Martin F-35 Lightning II** as a structural material for aircraft.^[56] CNRP still uses carbon fiber as the primary reinforcement,^[57] but the binding matrix is a carbon nanotube-filled epoxy.^[58]

See also

[**edit**]

- **Carbon fibers** – Material fibers about 5–10 μm in diameter composed of carbon
- **Composite repair** – Composite repair patch preparation and application
- **Mechanics of Oscar Pistorius's running blades** – Blades used by South African Paralympic runner Oscar Pistorius
- **Reinforced carbon–carbon** – Graphite-based composite material
- **Forged carbon fiber**
- **Carbon-ceramic**
- **Carbotanium**

References

[**edit**]

1. [^] **a b** Nguyen, Dinh; Abdullah, Mohammad Sayem Bin; Khawarizmi, Ryan; Kim, Dave; Kwon, Patrick (2020). "The effect of fiber orientation on tool wear in edge-trimming of carbon fiber reinforced plastics (CFRP) laminates". *Wear*. 450–451. Elsevier B.V: 203213. doi:**10.1016/j.wear.2020.203213**. ISSN **0043-1648**. S2CID **214420968**.
2. [^] Geier, Norbert; Davim, J. Paulo; Szalay, Tibor (1 October 2019). "**Advanced cutting tools and technologies for drilling carbon fibre reinforced polymer (CFRP) composites: A review**". *Composites Part A: Applied Science and Manufacturing*. **125**: 105552. doi:**10.1016/j.compositesa.2019.105552**. hdl:**10773/36722**.
3. [^] Dransfield, Kimberley; Baillie, Caroline; Mai, Yiu-Wing (1 January 1994). "**Improving the delamination resistance of CFRP by stitching—a review**". *Composites Science and Technology*. **50** (3): 305–317. doi:**10.1016/0266-3538(94)90019-1**.
4. [^] **a b** Kudo, Natsuko; Fujita, Ryohei; Oya, Yutaka; Sakai, Takenobu; Nagano, Hosei; Koyanagi, Jun (30 June 2023). "**Identification of invisible fatigue damage of thermosetting epoxy resin by non-destructive thermal measurement using entropy generation**". *Advanced Composite Materials*. **33** (2): 233–249. doi:**10.1080/09243046.2023.2230687**. ISSN **0924-3046**.
5. [^] Kopeliovich, Dmitri. "**Carbon Fiber Reinforced Polymer Composites**". Archived from the original on 14 May 2012.. substech.com
6. [^] Corum, J. M.; Battiste, R. L.; Liu, K. C; Ruggles, M. B. (February 2000). "**Basic Properties of Reference Crossply Carbon-Fiber Composite, ORNL/TM-2000/29, Pub57518**" (PDF). Oak Ridge National Laboratory. Archived (PDF) from the original on 27 December 2016.

7. ^ **a b c** Courtney, Thomas (2000). *Mechanical Behavior of Materials*. United States of America: Waveland Press, Inc. pp. 247–249. **ISBN 1-57766-425-6**.
8. ^ **a b c d e f** Chawla, Krishan (2013). *Composite Materials*. United States of America: Springer. **ISBN 978-0-387-74364-6**.
9. ^ **a b** Liao, Binbin; Wang, Panding; Zheng, Jinyang; Cao, Xiaofei; Li, Ying; Ma, Quanjin; Tao, Ran; Fang, Daining (1 September 2020). **"Effect of double impact positions on the low velocity impact behaviors and damage interference mechanism for composite laminates"**. *Composites Part A: Applied Science and Manufacturing*. **136**: 105964. doi:**10.1016/j.compositesa.2020.105964**. ISSN **1359-835X**.
10. ^ Ma, Binlin; Cao, Xiaofei; Feng, Yu; Song, Yujian; Yang, Fei; Li, Ying; Zhang, Deyue; Wang, Yipeng; He, Yuting (15 February 2024). **"A comparative study on the low velocity impact behavior of UD, woven, and hybrid UD/woven FRP composite laminates"**. *Composites Part B: Engineering*. **271**: 111133. doi: **10.1016/j.compositesb.2023.111133**. ISSN **1359-8368**.
11. ^ Aminakbari, Nariman; Kabir, Mohammad Zaman; Rahai, Alireza; Hosseinnia, Amirali (1 January 2024). **"Experimental and Numerical Evaluation of GFRP-Reinforced Concrete Beams Under Consecutive Low-Velocity Impact Loading"**. *International Journal of Civil Engineering*. **22** (1): 145–156. Bibcode: **2024IJCE...22..145A**. doi:**10.1007/s40999-023-00883-9**. ISSN **2383-3874**.
12. ^ Ray, B. C. (1 June 2006). "Temperature effect during humid ageing on interfaces of glass and carbon fibers reinforced epoxy composites". *Journal of Colloid and Interface Science*. **298** (1): 111–117. Bibcode:**2006JCIS..298..111R**. doi: **10.1016/j.jcis.2005.12.023**. PMID **16386268**.
13. ^ Almudaihesh, Faisel; Holford, Karen; Pullin, Rhys; Eaton, Mark (1 February 2020). **"The influence of water absorption on unidirectional and 2D woven CFRP composites and their mechanical performance"**. *Composites Part B: Engineering*. **182**: 107626. doi:**10.1016/j.compositesb.2019.107626**. ISSN **1359-8368**. S2CID **212969984**. Archived from the original on 1 October 2021. Retrieved 1 October 2021 .
14. ^ Guzman, Enrique; Cugnoni, Joël; Gmür, Thomas (May 2014). "Multi-factorial models of a carbon fibre/epoxy composite subjected to accelerated environmental ageing". *Composite Structures*. **111**: 179–192. doi: **10.1016/j.compstruct.2013.12.028**.
15. ^ Yari, Mehdi (24 March 2021). **"Galvanic Corrosion of Metals Connected to Carbon Fiber Reinforced Polymers"**. corrosionpedia.com. Archived from the original on 24 June 2021. Retrieved 21 June 2021.
16. ^ **"How is it Made"**. Zoltek. Archived from the original on 19 March 2015. Retrieved 26 March 2015.
17. ^ Syed Mobin, Syed Mobin; Azgerpasha, Shaik (2019). **"Tensile Testing on Composite Materials (CFRP) with Adhesive"** (PDF). *International Journal of Emerging Science and Engineering*. **5** (12): 6. Archived (PDF) from the original on 21 August 2022. Retrieved 21 August 2022 – via IJES.
18. ^ Glass Companies, Molded Fiber (2018), **Technical Design Guide for FRP Composite Products and Parts** (PDF), vol. 1, p. 25, archived from **the original**

- (PDF) on 21 August 2022, retrieved 21 August 2022
19. ^ Unknown, Chris (22 January 2020). **"Composite Manufacturing Methods"**. Explore Composites!. **Archived** from the original on 21 August 2022. Retrieved 21 August 2022.
 20. ^ **"Cutting of Fiber-Reinforced Composites: Overview"**. Sollex. 6 March 2025. Retrieved 31 March 2025.
 21. ^ **"Taking the lead: A350XWB presentation"** (PDF). EADS. December 2006. Archived from the original on 27 March 2009.
 22. ^ **"AERO – Boeing 787 from the Ground Up"**. Boeing. 2006. **Archived** from the original on 21 February 2015. Retrieved 7 February 2015.
 23. ^ Pora, Jérôme (2001). **"Composite Materials in the Airbus A380 – From History to Future"** (PDF). Airbus. **Archived** (PDF) from the original on 6 February 2015. Retrieved 7 February 2015.
 24. ^ Machado, Miguel A.; Antin, Kim-Niklas; Rosado, Luís S.; Vilaça, Pedro; Santos, Telmo G. (November 2021). **"High-speed inspection of delamination defects in unidirectional CFRP by non-contact eddy current testing"**. *Composites Part B: Engineering*. **224**: 109167. doi:10.1016/j.compositesb.2021.109167.
 25. ^ Machado, Miguel A.; Antin, Kim-Niklas; Rosado, Luís S.; Vilaça, Pedro; Santos, Telmo G. (July 2019). **"Contactless high-speed eddy current inspection of unidirectional carbon fiber reinforced polymer"**. *Composites Part B: Engineering*. **168**: 226–235. doi:10.1016/j.compositesb.2018.12.021.
 26. ^ Antin, Kim-Niklas; Machado, Miguel A.; Santos, Telmo G.; Vilaça, Pedro (March 2019). **"Evaluation of Different Non-destructive Testing Methods to Detect Imperfections in Unidirectional Carbon Fiber Composite Ropes"**. *Journal of Nondestructive Evaluation*. **38** (1). doi:10.1007/s10921-019-0564-y. ISSN 0195-9298.
 27. ^ Guzman, Enrique; Gmür, Thomas (dir.) (2014). **A Novel Structural Health Monitoring Method for Full-Scale CFRP Structures** (PDF) (Thesis). EPFL PhD thesis. doi:10.5075/epfl-thesis-6422. **Archived** (PDF) from the original on 25 June 2016.
 28. ^ **"Engines"**. *Flight International*. 26 September 1968. **Archived** from the original on 14 August 2014.
 29. ^ Szondy, David (28 March 2025). **"Airbus previews next-gen airliner with bird-inspired wings"**. *New Atlas*. Retrieved 7 April 2025.
 30. ^ **"Red Bull's How To Make An F1 Car Series Explains Carbon Fiber Use: Video"**. motorauthority. 25 September 2013. **Archived** from the original on 29 September 2013. Retrieved 11 October 2013.
 31. ^ Henry, Alan (1999). **McLaren: Formula 1 Racing Team**. Haynes. ISBN 1-85960-425-0.
 32. ^ Howard, Bill (30 July 2013). **"BMW i3: Cheap, mass-produced carbon fiber cars finally come of age"**. *Extreme Tech*. **Archived** from the original on 31 July 2015. Retrieved 31 July 2015.
 33. ^ Petrány, Máté (17 March 2014). **"Michelin Made Carbon Fiber Wheels For Citroën Back In 1971"**. *Jalopnik*. **Archived** from the original on 18 May 2015. Retrieved 31 July 2015.

34. ^ L:aChance, David (April 2007). **"Reinventing the Wheel Leave it to Citroën to bring the world's first resin wheels to market"**. Hemmings. **Archived** from the original on 6 September 2015. Retrieved 14 October 2015.
35. ^ Ismail, N. **"Strengthening of bridges using CFRP composites."** najif.net.
36. ^ Rahman, S. (November 2008). **"Don't Stress Over Prestressed Concrete Cylinder Pipe Failures"**. Opflow Magazine. **34** (11): 10–15. **Bibcode:** 2008Opflo..34k..10R. **doi:**10.1002/j.1551-8701.2008.tb02004.x. **S2CID** 134189821. **Archived** from the original on 2 April 2015.
37. ^ Pike, Carolyn M.; Grabner, Chad P.; Harkins, Amy B. (4 May 2009). **"Fabrication of Amperometric Electrodes"**. Journal of Visualized Experiments (27). **doi:** 10.3791/1040. **PMC** 2762914. **PMID** 19415069.
38. ^ **"ICC and Kookaburra Agree to Withdrawal of Carbon Bat"**. NetComposites. 19 February 2006. Archived from the original on 28 September 2018. Retrieved 1 October 2018.
39. ^ **"Carbon Technology"**. Look Cycle. **Archived** from the original on 30 November 2016. Retrieved 30 November 2016.
40. ^ **"The Perils of Progress"**. Bicycling Magazine. 16 January 2012. Archived from the original on 23 January 2013. Retrieved 16 February 2013.
41. ^ **"Busted Carbon"**. **Archived** from the original on 30 November 2016. Retrieved 30 November 2016.
42. ^ Zhao, Z.; Gou, J. (2009). **"Improved fire retardancy of thermoset composites modified with carbon nanofibers"**. Sci. Technol. Adv. Mater. **10** (1): 015005. **Bibcode:**2009STAdM..10a5005Z. **doi:**10.1088/1468-6996/10/1/015005. **PMC** 5109595. **PMID** 27877268.
43. ^ **"Carbon fibre reinforced plastic bogies on test"**. Railway Gazette. 7 August 2016. **Archived** from the original on 8 August 2016. Retrieved 9 August 2016.
44. ^ Lomov, Stepan V.; Gorbatiikh, Larissa; Kotanjac, Ćirilko; Koissin, Vitaly; Houille, Matthieu; Rochez, Olivier; Karahan, Mehmet; Mezzo, Luca; Verpoest, Ignaas (February 2011). **"Compressibility of carbon woven fabrics with carbon nanotubes/nanofibres grown on the fibres"** (PDF). Composites Science and Technology. **71** (3): 315–325. **doi:**10.1016/j.compscitech.2010.11.024.
45. ^ Hans, Kreis (2 July 2014). **"Carbon woven fabrics"**. compositesplaza.com. Archived from the original on 2 July 2018. Retrieved 2 January 2018.
46. ^ Ali Nahran, Shakila; Saharudin, Mohd Shahneel; Mohd Jani, Jaronie; Wan Muhammad, Wan Mansor (2022). **"The Degradation of Mechanical Properties Caused by Acetone Chemical Treatment on 3D-Printed PLA-Carbon Fibre Composites"**. In Ismail, Azman; Dahalan, Wardiah Mohd; Öchsner, Andreas (eds.). Design in Maritime Engineering. Advanced Structured Materials. Vol. 167. Cham: Springer International Publishing. pp. 209–216. **doi:**10.1007/978-3-030-89988-2_16. **ISBN** 978-3-030-89988-2. **S2CID** 246894534.
47. ^ **"Polyamid CF Filament – 3D Druck mit EVO-tech 3D Druckern"** [Polyamide CF Filament – 3D printing with EVO-tech 3D printers] (in German). Austria: EVO-tech. **Archived** from the original on 30 April 2019. Retrieved 4 June 2019.
48. ^ Schinner, G.; Brandt, J.; Richter, H. (1 July 1996). **"Recycling Carbon-Fiber-Reinforced Thermoplastic Composites"**. Journal of Thermoplastic Composite

- Materials. **9** (3): 239–245. doi:[10.1177/089270579600900302](https://doi.org/10.1177/089270579600900302). ISSN 0892-7057.
49. ^ Roux, Maxime; Eguémann, Nicolas; Dransfeld, Clemens; Thiébaud, Frédéric; Perreux, Dominique (1 March 2017). **"Thermoplastic carbon fibre-reinforced polymer recycling with electrodynamical fragmentation: From cradle to cradle"**. *Journal of Thermoplastic Composite Materials*. **30** (3): 381–403. doi:[10.1177/0892705715599431](https://doi.org/10.1177/0892705715599431). ISSN 0892-7057.
50. ^ Bernatas, Rebecca; Dagréou, Sylvie; Despax-Ferreres, Auriane; Barasinski, Anaïs (2021). **"Recycling of fiber reinforced composites with a focus on thermoplastic composites"**. *Cleaner Engineering and Technology*. **5**: 100272. Bibcode:[2021CEngT...500272B](#). doi:[10.1016/j.clet.2021.100272](https://doi.org/10.1016/j.clet.2021.100272).
51. ^ Naqvi, S. R.; Prabhakara, H. Mysore; Bramer, E. A.; Dierkes, W.; Akkerman, R.; Brem, G. (1 September 2018). **"A critical review on recycling of end-of-life carbon fibre/glass fibre reinforced composites waste using pyrolysis towards a circular economy"**. *Resources, Conservation and Recycling*. **136**: 118–129. Bibcode:[2018RCR...136..118N](#). doi:[10.1016/j.resconrec.2018.04.013](https://doi.org/10.1016/j.resconrec.2018.04.013). ISSN 0921-3449.
52. ^ Zhang, Jin; Chevali, Venkata S.; Wang, Hao; Wang, Chun-Hui (15 July 2020). **"Current status of carbon fibre and carbon fibre composites recycling"**. *Composites Part B: Engineering*. **193**: 108053. doi:[10.1016/j.compositesb.2020.108053](https://doi.org/10.1016/j.compositesb.2020.108053). ISSN 1359-8368.
53. ^ Cousins, Dylan S.; Suzuki, Yasuhito; Murray, Robynne E.; Samaniuk, Joseph R.; Stebner, Aaron P. (1 February 2019). **"Recycling glass fiber thermoplastic composites from wind turbine blades"**. *Journal of Cleaner Production*. **209**: 1252–1263. Bibcode:[2019JCPro.209.1252C](#). doi:[10.1016/j.jclepro.2018.10.286](https://doi.org/10.1016/j.jclepro.2018.10.286). ISSN 0959-6526.
54. ^ Bernatas, Rebecca; Dagréou, Sylvie; Despax-Ferreres, Auriane; Barasinski, Anaïs (1 December 2021). **"Recycling of fiber reinforced composites with a focus on thermoplastic composites"**. *Cleaner Engineering and Technology*. **5**: 100272. Bibcode:[2021CEngT...500272B](#). doi:[10.1016/j.clet.2021.100272](https://doi.org/10.1016/j.clet.2021.100272). ISSN 2666-7908.
55. ^ **"Zyvex Performance Materials Launch Line of Nano-Enhanced Adhesives that Add Strength, Cut Costs"** (PDF) (Press release). Zyvex Performance Materials. 9 October 2009. Archived from [the original](#) (PDF) on 16 October 2012. Retrieved 26 March 2015.
56. ^ Trimble, Stephen (26 May 2011). **"Lockheed Martin reveals F-35 to feature nanocomposite structures"**. *Flight International*. Archived from the original on 30 May 2011. Retrieved 26 March 2015.
57. ^ Pozegic, T. R.; Jayawardena, K. D. G. I.; Chen, J-S.; Anguita, J. V.; Balocchi, P.; Stolojan, V.; Silva, S. R. P.; Hamerton, I. (1 November 2016). **"Development of sizing-free multi-functional carbon fibre nanocomposites"**. *Composites Part A: Applied Science and Manufacturing*. **90**: 306–319. doi:[10.1016/j.compositesa.2016.07.012](https://doi.org/10.1016/j.compositesa.2016.07.012). hdl:[1983/9e3d463c-20a8-4826-89f6-759e950f43e6](#). ISSN 1359-835X. S2CID [137846813](#). Archived from the original on 1 October 2021. Retrieved 1 October 2021.
58. ^ **"AROVEX™ Nanotube Enhanced Epoxy Resin Carbon Fiber Prepreg – Material Safety Data Sheet"** (PDF). Zyvex Performance Materials. 8 April 2009.

External links

[edit]

 image not found or type unknown

Wikimedia Commons has media related to ***Carbon fiber reinforced plastic***.

- **Japan Carbon Fiber Manufacturers Association (English)**
- **Engineers design composite bracing system for injured Hokie running back Cedric Humes**
- **The New Steel** a 1968 *Flight* article on the announcement of carbon fiber
- **Carbon Fibres – the First Five Years** A 1971 *Flight* article on carbon fiber in the aviation field

Authority control databases: **National**  **Get on this**  **Edit this at Wikidata**

About Cook County

Driving Directions in Cook County

Driving Directions From 42.088525008778, -88.079435634324 to

Driving Directions From 42.021124436568, -88.109125186152 to

Driving Directions From 42.017845685371, -88.11591807218 to

Driving Directions From 42.084324223519, -88.137710099374 to

Driving Directions From 42.10843482977, -88.114090738222 to

Driving Directions From 42.086153671225, -88.19640031169 to

Driving Directions From 42.051159627372, -88.202951526236 to

Driving Directions From 42.008657936699, -88.152725208607 to

Driving Directions From 42.007242948498, -88.153060682778 to

Driving Directions From 42.073881347839, -88.179224443136 to

<https://www.google.com/maps/place/@42.050000207566,-88.075050390596,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/place/@42.087798734568,-88.063295005626,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/place/@42.10843482977,-88.114090738222,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/place/@42.050966333631,-88.065085692084,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/place/@42.03783000352,-88.074000387298,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/place/@42.047694157891,-88.091046817967,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/place/@42.010753136556,-88.109359678334,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/place/@42.056354483873,-88.088327608895,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/place/@42.102108978802,-88.091450952786,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/place/@42.042207985309,-88.186095527361,25.2z/data=!4m6!3m5!1sNone!8m2!3d42.0637725!4d-88.1396465!16s%2F>

<https://www.google.com/maps/dir/?api=1&origin=42.042207985309,-88.186095527361&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+Stonington+Illinois&travelmode=driving&query=foundation+settlement+sign>

<https://www.google.com/maps/dir/?api=1&origin=42.011697190191,-88.159742980637&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+Stonington+Illinois&travelmode=transit&query=structural+engineer+consult>

<https://www.google.com/maps/dir/?api=1&origin=42.068719913035,-88.076011775936&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+Stonington+Illinois&travelmode=transit&query=foundation+stability+check>

<https://www.google.com/maps/dir/?api=1&origin=42.040913746131,-88.212085693635&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+Stonington+Illinois&travelmode=transit&query=helical+pier+installation+Sch>

<https://www.google.com/maps/dir/?api=1&origin=42.002740342082,-88.143950765717&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+Stonington+Illinois&travelmode=transit&query=sprayed+urethane+foam+lif>

<https://www.google.com/maps/dir/?api=1&origin=42.10843482977,-88.114090738222&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+United+Structural+Systems+of+Illinois&travelmode=transit&query=house+leveling+service+Des>

<https://www.google.com/maps/dir/?api=1&origin=42.089226014242,-88.21676191398&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+United+Structural+Systems+of+Illinois&travelmode=driving&query=crawl+space+underpinning+>

<https://www.google.com/maps/dir/?api=1&origin=42.076323560785,-88.219373904701&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+United+Structural+Systems+of+Illinois&travelmode=transit&query=slab+foundation+lifting+Hoff>

<https://www.google.com/maps/dir/?api=1&origin=42.097395420237,-88.146014933305&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+United+Structural+Systems+of+Illinois&travelmode=transit&query=sinking+basement+floor+Bo>

<https://www.google.com/maps/dir/?api=1&origin=42.027868101227,-88.201484266296&destination=%2C+2124+Stonington+Ave%2C+Hoffman+Estates%2C+United+Structural+Systems+of+Illinois&travelmode=driving&query=water+intrusion+prevention->

United Structural Systems of Illinois, Inc

Phone : +18473822882

City : Hoffman Estates

State : IL

Zip : 60169

Address : 2124 Stonington Ave

Google Business Profile

Company Website : <https://www.unitedstructuralsystems.com/>

USEFUL LINKS

foundation crack repair Chicago

residential foundation inspection

[home foundation leveling](#)

[basement foundation repair](#)

[Sitemap](#)

[Privacy Policy](#)

[About Us](#)

Follow us